

1N248B, C thru 1N250B, C

1N1191 thru 1N1198

1N1195A thru 1N1198A

1N3213, 1N3214



CASE 42
(DO-5)

Medium current silicon rectifiers. Unique double-case construction consists of hermetically sealed inner metallic case surrounded by molded external case; provides highest degree of ruggedness and reliability. Type numbers shown have cathode connected to case, but reverse-polarity units can be obtained by adding suffix "R" to standard type number, e.g. 1N248BR.

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Peak Repetitive Reverse Voltage and DC Blocking Voltage 1N248B, 1N1191 1N248C 1N249B, 1N1192 1N249C 1N1193 1N250B, 1N1194 1N250C 1N1195, 1N1195A 1N1196, 1N1196A 1N1197, 1N1197A, 1N3213 1N1198, 1N1198A, 1N3214	V_{RM} (rep) V_R	 50 55 100 110 150 200 220 300 400 500 600	Volts
RMS Reverse Voltage 1N248B, 1N1191 1N248C 1N249B, 1N1192 1N249C 1N1193 1N250B, 1N1194 1N250C 1N1195, 1N1195A 1N1196, 1N1196A 1N1197, 1N1197A, 1N3213 1N1198, 1N1198A, 1N3214	V_R	35 38.5 70 77 105 140 154 210 280 350 420	Volts
Average 1/2-Wave Rectified Forward Current (Resistive Load, 60 Hz, $T_C = 150^\circ\text{C}$)	I_O	20	Amp
Peak Repetitive Forward Current ($T_C = 150^\circ\text{C}$)	I_{FM} (rep)	90	Amp
Peak Surge Current ($T_C = 150^\circ\text{C}$, superimposed on Rated Current at Rated Voltage, 1/2-Cycle, 1/120 sec)	I_{FM} (surge)	350	Amp